

इंटरनेट

Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

"जानने का अधिकार, जीने का अधिकार" Mazdoor Kisan Shakti Sangathan "The Right to Information, The Right to Live"

"पुराने को छोड नये के तरफ" Jawaharlal Nehru "Step Out From the Old to the New"

IS 14474-1 (1997): Mobile Cranes - Experimental Determination of Crane Performance, Part 1: Tipping Loads and Radii [MED 14: Cranes, Lifting Chains and Related Equipment]

"ज्ञान से एक नये भारत का निर्माण″ Satyanarayan Gangaram Pitroda "Invent a New India Using Knowledge"

RIGHT TO INFORMATION "ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता Bhartrhari-Nītiśatakam "Knowledge is such a treasure which cannot be stolen"



मानक







6111111

Made Available By Public.Resource.Org







BLANK PAGE



PROTECTED BY COPYRIGHT

IS 14474 (Part 1): 1997 ISO 11662-1: 1995

भारतीय मानक

गतिशील क्रेन – क्रेन को कार्यकारिता का प्रायोगिक रूप से ज्ञात करना

भाग 1 टिपिंग लोड और राडी

Indian Standard

MOBILE CRANES — EXPERIMENTAL DETERMINATION OF CRANE PERFORMANCE

PART 1 TIPPING LOADS AND RADII

ICS 53.020.20

© BIS 1997

BUREAU OF INDIAN STANDARDS MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002

NATIONAL FOREWORD

This Indian Standard which is identical with ISO 11662-1 : 1995 'Mobile cranes — Experimental determination of crane performance — Part 1 : Tipping loads and radii', issued by International Organization for Standardization (ISO), was adopted by the Bureau of Indian Standards on the recommendations of the Cranes, Lifting Chains and Its Related Equipment Sectional Committee, and approval of the Heavy Mechanical Engineering Division Council.

The text of ISO standard has been approved for publication as Indian Standard without deviations. Certain terminology and conventions are, however, not identical to those used in Indian Standards. Attention is particularly drawn to the following:

- a) Wherever the words 'International Standard' appear referring to this standard, they should be read as 'Indian Standard'.
- b) Comma (,) has been used as a decimal marker while in Indian Standards, the current practice is to use a full stop (.) as a decimal marker.

In this adopted standard, reference appears to certain International Standards for which Indian Standards also exist. The corresponding Indian Standard which is to be substituted in its place was listed below along with its degree of equivalence for the editions indicated:

International Standard	Corresponding Indian Standard	Degree of Equivalence
*ISO 4306-2 : 1994	IS 13473 (Part 2) : 1992 Cranes — Vocabulary : Part 2 Mobile cranes	Technically Equivalent

In reporting the results of a test or analysis made in accordance with this standard, if the final value, observed or calculated, is to be rounded off, it shall be done in accordance with IS 2 : 1960 'Rules for rounding off numerical values (*revised*)'.

^{*}ISO 4306-2 : 1985 was adopted as IS 13473 (Part 2) : 1992. Now, ISO 4306-2 has been revised in 1994. Hence the degree of equivalence for corresponding Indian Standard is shown as Technically Equivalent.

Indian Standard MOBILE CRANES — EXPERIMENTAL DETERMINATION OF CRANE PERFORMANCE

PART 1 TIPPING LOADS AND RADII

1 Scope

This part of ISO 11662 specifies a test method to determine the maximum capacity of a mobile crane to counterbalance loads applied on its hook block.

The test is applicable for cranes whose capacity to support loads is based on its static resistance to overturning. The test shall not be used on cranes whose capacity is based on structural strength or on limitations due to available load hoist, jib hoist or jib telescope capability.

This part of ISO 11662 applies to all mobile cranes as defined in ISO 4306-2.

2 Normative reference

The following standard contains provisions which, through reference in this text, constitute provisions of this part of ISO 11662. At the time of publication, the edition indicated was valid. All standards are subject to revision, and parties to agreements based on this part of ISO 11662 are encouraged to investigate the possibility of applying the most recent edition of the standard indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 4306-2:1994, Lifting appliances — Vocabulary — Part 2: Mobile cranes.

3 Definitions

For the purpose of this part of ISO 11662, the following definitions apply.

3.1 balance condition: Condition of crane loading in which the load moment acting to overturn the crane is equal to the maximum moment of the crane available to resist overturning.

3.2 axis of rotation: Vertical line through the axis around which the crane superstructure rotates before load is applied to the crane hook.

3.3 load: Force acting to unbalance a crane, resulting from the gravitational force created by the hook block itself and the charges suspended from it.

3.4 radius of load: Horizontal distance between the point from which the radius is measured projected onto the supporting surface before loading, and the centre of the vertical hoist line or tackle after loading.

4 Principle

The load is applied by freely suspending from the crane hook block a weight of predetermined magnitude and either lengthening the radius until crane stability is overcome, or adding incremental weights using a fixed radius until crane stability is overcome.

The tester should ensure that tests are made in the least stable direction for each rating under test.

5 Apparatus

5.1 Supporting surface, of concrete or other firm material, sufficiently large to provide for unobstructed testing.

5.2 Means for measuring the load radius to an accuracy of ± 1 % or $\pm 0,15$ m, whichever is smaller.

5.3 Tyre pressure gauge, having an accuracy of ± 3 % of the measured pressure.

5.4 Means for measuring the horizontal distance from the axis of rotation to the centre of gravity of the load.

5.5 Means for measuring the mass of test weights, hook block, slings and ancillary equipment (excluding the hoist rope), to an accuracy of ± 1 % of the measured load.

5.6 Test weights, hook blocks, slings and ancillary equipment (excluding the hoist rope) of mass known to within ± 1 %.

6 Test conditions

6.1 For the purpose of testing, the crane shall be equipped with working equipment suitable for operation with the rated load.

6.2 When testing cranes on pneumatic tyres or crawler equipment, the appliance shall be placed on a firm level surface (≤ 1 % gradient).

6.3 When testing pneumatic-tyred equipment while operating on tyres, the tyres shall be inflated to within ± 3 % of the pressure stipulated by the manufacturer, and all wheels shall be in the ahead position.

Conditions for tyre support shall comply with manufacturers requirements.

6.4 For conducting tests of cranes with outriggers in the "on outriggers" condition, the crane shall be level ($\leq 1\%$ gradient).

6.4.1 When outriggers are used in the course of testing pneumatic-tyred cranes, the crane shall be raised by the outriggers so as to provide clearance between the ground and all the wheels or to relieve all wheels of the weight of the crane unless the suspension design is such that the tyres stay on the ground when outriggers are set.

6.4.2 When outriggers are used in the course of testing crawler cranes, the crane shall be installed so as to ensure firm bearing of the outriggers on the supporting surface.

6.5 The fuel tank shall be no more than one-third full. Coolant, lubricating oil and hydraulic fluids shall be at the operating levels specified by the manufacturer.

6.6 Wind direction should be such that it does not increase the stability of the crane.

7 Test procedure

7.1 Test preparation

7.1.1 Service and adjust the crane as applicable according to the manufacturer's recommendation to assure specified conditions of

- a) lubrication;
- b) fuel supply;
- c) tyre inflation;
- d) coolant supply;
- e) track tension;
- f) bolts, pins, cable fittings and other load-bearing components;
- g) clutches, brakes and other power transmission components;
- h) boom length and rigging;
- j) crane level (≤ 1 % gradient).

7.1.2 A competent operator shall operate the crane. In the absence of specific recommendations, a new machine should be operated for at least 4 h to ensure proper function of the machine. At the conclusion of this initial operation, service and adjust the machine to the specified conditions.

7.1.3 Locate the crane on the test course in position for loading and actuate the travel brakes.

7.1.4 Set outriggers, if used, and jack the crane to a position in which the tyres or tracks within the boundary of the outriggers are unloaded.

7.1.5 Vertically project the superstructure axis-of-rotation onto the surface of the test course and mark its location.

7.2 Test measurements

7.2.1 Prepare test load, including test weights, hook block, slings and any other ancillary equipment, such as load basket, to make up the specified load mass to within ± 1 %. Record this value.

7.2.2 With the crane superstructure in its least stable configuration for the specified position, hoist the load free from the test surface at a radius at which the crane is stable; then boom down a small amount to increase the radius. Keep the load within 0,1 m of the test surface at all times to prevent excessive tipping. If the crane will support the load at the adjusted radius without tipping, measure and record the new radius. Repeat the procedure until the balance point is reached. When the balance point is reached, record the mass of the load and radius of the load.

NOTE 1 The final adjustment of the balance point may be made by adding small increments of mass rather than increasing the radius.

7.2.3 Alternatively, measure the radius of load and add small increments of mass to the load until the load overcomes the stability of the crane. The radius of load and load mass last employed, before the stability of the crane was overcome, shall be recorded as the balance point condition.

8 Plotting of capacity curve

Where it is desired to determine the balance point capacities of a crane throughout a range of loads or radii, follow procedures as outlined in 7.2, making sure that the load and radius are determined for each extreme of the chosen range and at a sufficient number of intermediate points to permit plotting a curve. Plot a curve showing the maximum capacity of the crane with the load, in kilograms, as ordinate and radius, in metres, as abscissa. Use a representative number of boom lengths for a given capacity chart.

9 Test report

Record a complete description of the crane, positions for the test, data for the tipping load and the radius of load on test data sheets. See table 1 and figures 1 and 2 for examples of test data sheets.

IS 14474 (Part 1): 1997 ISO 11662-1: 1995

Table 1 — Data sheet for mobile crane description and balance points

Manufacturer	Model	Serial No.
Condition: New 🗌	Used 🗌	Hours of previous use
Mounting: Type		Size
Tyres: Size	Radial Ply	Pressure (kPa)
Boom: Type		Length (m)
Boom jib: Type	Length (m)	Angle to the boom/ground ¹⁾
Engine: Manufacturer	Model	Serial No.
Counterweight: Type		Mass (kg)
Test method: Suspended weights 🗌		Anchor 🗌

	Balance points				
Position of superstructure	Without outriggers		With	With outriggers	
	Load	Radius	Load	Radius	
	(kg)	(m)	(kg)	(m)	
		· · · · · ·			
		·····			
				·	
				·······	
Remarks:					
Operator:			Date of test:		
I) When fly jib is fixed, the angle is to	the boom; when f	y jib is luffing, the ang	le is to the ground.		

.



Figure 1 — Data sheet for physical dimensions of undercarriage chassis for wheel-mounted cranes



Figure 2 — Data sheet for physical dimensions of undercarriage chassis for carrier-mounted and crawler-mounted cranes

IS 14474 (Part 1): 1997 ISO 11662-1: 1995

•

Annex A

(informative)

Bibliography

[1] ISO 4305:1991, Mobile cranes — Determination of stability.

Bureau of Indian Standards

BIS is a statutory institution established under the *Bureau of Indian Standards Act*, 1986 to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

Copyright

Headquarters:

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Director (Publications), BIS.

Review of Indian Standards

Amendments are issued to standards as the need arises on the basis of comments. Standards are also reviewed periodically; a standard along with amendments is reaffirmed when such review indicates that no changes are needed; if the review indicates that changes are needed, it is taken up for revision. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition by referring to the latest issue of 'BIS Handbook' and 'Standards : Monthly Additions'.

This Indian Standard has been developed from Doc : No. HMD 14 (0413).

Amendments Issued Since Publication

Amend No.	Date of Issue	Text Affected
		· ·
		·

BUREAU OF INDIAN STANDARDS

Manak Bhavan, 9 Bahadur Shah Zafar Marg, New Delhi 110002 Telephones : 323 01 31, 323 94 02, 323 33 75	Telegrams: Manaksanstha (Common to all offices)	
Regional Offices:	Telephone	
Central : Manak Bhavan, 9 Bahadur Shah Zafar Marg NEW DELHI 110002	323 76 17 323 38 41	
Eastern : 1/14 C. I. T. Scheme VII M, V. I. P. Road, Maniktola CALCUTTA 700054	337 84 99, 337 85 61 337 86 26, 337 86 62	
Northern : SCO 335-336, Sector 34-A, CHANDIGARH 160022	60 38 43 60 20 25	
Southern : C. I. T. Campus, IV Cross Road, CHENNAI 600113	235 02 16, 235 04 42 235 15 19, 235 23 15	
Western : Manakalaya, E9 MIDC, Marol, Andheri (East) MUMBAI 400093	832 92 95, 832 78 58 832 78 91, 832 78 92	
Branches : AHMADABAD. BANGALORE. BHOPAL. COIMBATORE FARIDABAD GHAZIABAD GUWAHATI	BHUBANESHWAR. HYDERABAD JAIPUR	

KANPUR, LUCKNOW, NAGPUR, PATNA, PUNE, THIRUVANANTHAPURAM,

Printed at New India Printing Press, Khurja, India